JACKET P59





PPE TECHNICAL FILE



JACKET FOR COLD PROTECTION

EUROPEAN STANDARDS

EN 340

EN 342:2004 Cat. II

EC CERTIFICATE Nº 0072/282/162/04/14/0024

PERFORMANCE LEVELS

TEAR RESISTANCE OUTER FABRIC | COMPLY EVAPORATIVE RESISTANCE R_{ET} | 36 M² PA/W AIR PERMEABILITY (ISO 9237) | CLASS 2 THERMAL INSULATION I_{CLER} | 0.310² K/W (B)

PPE TECHNICAL FEATURES

- PROTECTION AGAINST SUBZERO TEMPERATURES
- FUR COLLAR
- FRONT ZIPPER WITH PROTECTIVE FLAP AND PRESS STUDS
- 1 CHEST POCKET
- 2 LOWER POCKETS WITH THERMAL INSULATION
- KNITTED CUFFS FOR PERFECT FIT
- THERMAL INSULATION AND QUILTED LINING
- TEMPERATURE IS MAINTAINED IN WET ENVIRONMENTS
- ullet resistant, breathable, easy maintenance
- \bullet Certified PPE according to standard en342 for temperature below 5º C.

PACKAGING

CARDBOARD BOX

ALLERGIES

ANTI-ALLERGIC FINISH, DESIGNED FOR HUMAN USE

STORAGE INSTRUCTIONS

STORE IN A DRY PLACE

PROTECT AGAINST HIGH TEMPERATURES AND UV RAYS EXPOSURE ONCE REMOVED FROM THE ORIGINAL PACKAGING, IT CAN BE STORED ON A HANGER

USE INSTRUCTIONS

KEEP THE PPE CLOSED WHEN IN USE FOR EFFECTIVE THERMAL PROTECTION PPE THERMAL INSULATION CAN BE AFFECTED BY AN INAPPROPRIATE CLEANING

DO NOT REMOVE THE LABEL
RESPECT CARE INSTRUCTIONS

WASH AND CARE INSTRUCTIONS

THIS GARMENT SHOULD BE HANDWASHED OR MACHINE LAUNDERED ON A GENTLE CYCLE. DO NOT BLEACH, TUMBLE DRY, IRON OR DRY CLEAN



GARMENT PROTECTION	LIMITATION	LIGHT ACTIVITY	MEDIUM ACTIVITY
ACTIVITY EXPOSURE	1 HOUR	- 15 º C	- 32 º C
	8 HOURS	-1 º C	- 19 º C

PPE COMPOSITION

COLOURS

● FUR 100% ACRYLIC FIBRE 700 GR/M²

● KNITTING 100% ACRYLIC FIBRE

OUTER FABRIC
 LINING
 THERMAL INSULATION
 THERMAL INSULATION
 TOW POLYESTER 220 GR/M²

BLACK, ROYAL, NAVY, GREEN, BRING GREEN, RED, ORANGE, WHITE, GREY,

CHINO, CARAMEL, BROWN

• SIZES XXS-XXXL