





# **JACKET P125L**



### **EUROPEAN STANDARDS**

EN 342:2004 CAT II

Protective clothing - Ensembles and garments for protection against the cold ( < - 5° C) EN 340

Protective clothing – General Requirements EU Type-examination (Module B) n° 0072/282/162/06/97/0163

#### PPE TECHNICAL FEATURES

- · Long jacket
- · It can be produced with or without hood
- · When without hood, with knitted collar for thermal comfort
- Front zipper
- Two lower pockets with thermal insulation
- · Knitted cuffs for perfect fit
- Thermal insulation and guilted lining
- Temperature is maintained in humid environments
- · Resistant, breathable, easy maintenance

#### **PACKAGING**

Cardboard box

ALL FRGIES

Anti-allergic finish, designed for human use

#### STORAGE INSTRUCTIONS

Store in a dry place. Protect against high temperatures and UV rays exposure. Once removed from its original packaging, it can be stored on a hanger.

#### **USE INSTRUCTIONS**

Keep PPE closed when in use. Do not remove the conservation label. Respect the cleaning instructions on the label attached to the PPE. Not following washing instructions can significantly shorten the life of the PPE. The PPE must be kept in a good state of cleanliness and conservation. The PPE is water permeable.

## **TECHNICAL FILE**

#### PERFORMANCE LEVELS

Tear resistance outer fabric Evaporative Resistance Ret Air permeability (ISO 9237) Resistance to water penetration Thermal insulation Icler

Comply Level 3 Class 2

0,254 m<sup>2</sup> K/W (B)

Thermal insulation	Light activity  Exposure	Light activity  Exposure	Medium activity Exposure	Medium activity Exposure
I <sub>cler</sub> m <sup>2</sup> K/M	8 hours ° C	1 hour ° C	8 hours ° C	1 hour ° C
0,254	- 6° C	- 16° C	- 10° C	- 22° C

#### PPE COMPOSITION

 Outer fabric 100% nylon 62 gr/m<sup>2</sup> 100% polyester 62 gr/m<sup>2</sup> Linina 100% polyester 140 gr/m<sup>2</sup> · Thermal insulation • Knit 100% acrylic fibre

Colours Navy, white

Sizes XXS - XXXL

#### WASHING INSTRUCTIONS

Maximum washing temperature 40° C (normal process). Bleaching is not allowed. Do not tumble dry. Do not iron. Do not dry clean.











Refrigue Lda. E.N. 252 ao KM 11.330 – 2950-402 Palmela – Portugal T. +351 212 363 601 info@refrigue.pt